

# Gap-Seal

## Water Based Acrylic Gap Sealant



### Description

**SA Gap-Seal Acrylic Gap Sealant** is a flexible, one part, water based acrylic latex caulk for interior and exterior gaps and joints.

### Key performance Properties

- One part ready to use
- Paintable
- Water based / water clean-up
- 5 Star VOC compliant

### Applications

**SA Gap-Seal** displays excellent adhesion to concrete, masonry, wood, brick, plasterboard and interior cornices. Gap-Seal is ideal for sealing interior and exterior wall joints not subjected to significant joint movement or pooling of water.

### Specifications

Typical data values should not be used as specifications. Please contact Sealants Australasia for further information.

Property	Value
Colour	White
Specific Gravity	1.65 g/ml
Solids	85%
Application Temperature	5-40 °C
Shore A Hardness	40
100% Modulus	0.7 Mpa
Elongation At Break	200%
Skin Time -20°C/55%Rh	5 Minutes
Joint Movement Capability	±7.5%

### Sealants Australasia Pty Ltd

ABN 83 104 230 015 U4/52 Vinnicombe Drive Canning Vale Western Australia 6155  
Phone **08 9456 3627** Fax 08 9456 3927



# Gap-Seal

## Water Based Acrylic Gap Sealant

### Application

Cut nozzle at 45 Degree angle to desired bead width, and apply to substrate with sealant gun and tool within 5 minutes. Uncured sealant can be cleaned up with a damp cloth. For a neat appearance to the joint, use masking tape. Always remove masking tape before sealant has skinned over.

### Surface preparation

Surfaces must be clean, dry and free of dirt, grease, oil, rust and water. Do not use soap or detergent.

### Packaging

450gm Cartridges - Available in cartons of 20.  
Product Packed in Australia.

### Storage/Shelf life

The shelf life of **SA Gap-Seal** is 18 months if stored in a cool dry place. The storage temperature should not exceed 25°C as this will decrease shelf life.

### Health and safety

Avoid contact with skin, eyes and mouth. If in eyes, immediately flush with water for 15 minutes. If irritation persists seek medical attention. MSDS available on request.

**KEEP OUT OF REACH OF CHILDREN.**

### Limitations

**SA Gap-Seal** is not recommended for underwater applications or use in areas with excessive water pooling or weather exposure. Gap-Seal should not be used in applications where temperatures exceed 80°C

### Sealant Volume Calculator

Number of 450gm Cartridges = Joint Width (mm) x Joint depth (mm) x Joint length (m) x 1.15\* ÷ 292

*\* Please note: 1.15 Allows for 15% wastage. Joints are assumed rectangular*



**Available From:**

### Sealants Australasia Pty Ltd

ABN 83 104 230 015 U4/52 Vinnicombe Drive Canning Vale Western Australia 6155

Phone **08 9456 3627** Fax 08 9456 3927



**PLEASE NOTE:** Information contained and recommendations made herein apply to SA products alone. Such are based on research and data from other reliable sources and are believed at the time of print to be accurate. It is the purchaser's responsibility before using any product, to verify this data under their own operating conditions to determine if such product is suitable for their purposes.

[www.sealants.com.au](http://www.sealants.com.au)